

Comments for deployment operations:
Lodd satt ut sist
Comments for next recovery operations:

Instrumentsconfig						
#	Brand	Freq	AVG	celle	M-load	Start
1	RBR CTD	3s		204775		st. 01.07 12:00
2	RBRSolo T	1S		203552		st. 01.07 12:00
3	SBE56	6s				st. 01.07 12:00
4	Sig250	15min	120	2m	70%	st. 01.07 12:00
Rigging parts						
#	Type					Qty
1	Shackle galvanized steel 2T					9
2	Shackle galvanized steel 3.25T					4
3	Kevlar tau (8mm gul)					2x24.7
4	Strope					1x3m

Responsible for deployment and recovery operations:
Terje Hovland og Henrik Søyland

Subm. Weight [kg]	Net Buoyancy [kg]	Length [m]	Material / Object	Diagram	Depth [m]
					0 m
					20,7 m
	10	2.3	Vitrovex med Argos og T0		
	100	1.5	Vitrovex Glass sphere x4		23 m
		37,5	Dyneema tau 37,5mm		24,5 m
	100	2.5	Vitrovex Glass sphere x4		62
		37,5			64.5
	60	2	Signature 250		102m
		170	25m Dyneema, 5m+40m+100m kevlar		
	50	1	Vitrovex Glass sphere x4		
22		1	Ixsea acoustic release		
		1	Strope		
500		6	mooring+ chain		283 m